GSG500T

Braided sleeving // Glassfiber

Thermally pretreated, in addition to the good properties of pure glass fabric, there is less fraying at the cut edges, increased diameter stability when inserting cables. Slightly stiffer than GSG500.

Contact

Tel.: +49 (0) 9952 90911-0
email: sales@bastech.de
www.bastech.de

Technical Reference

Material	Fiberglass (E-Glas), thermally pre-treated	
Colors	Natural colors, colored identification threads can be incorporated on request.	
Packaging	On reels, cuto on demand	
Specification	Operating temp.:	-70°C to +500°V
	Flammability:	not flammable
	Tensil strength:	12 MPa
	Resistance to acids, alkalis, cleaning fluids, fuels, oils and salt water Fungus and rot formation:	excellent

Sizes and Ordering Codes

Ordering-Code	Inner-Ø 45° mm	Wall mm	reel length m	Ordering-Code	Inner-Ø 45° mm	Wall mm	reel length m
GSG500T-0,5-nt	0,5		200	GSG500T-12-nt	12		50
GSG500T-0,8-nt	0,8		200	GSG500T-14-nt	14		50
GSG500T-1-nt	1		200	GSG500T-16-nt	16		50
GSG500T-1,5-nt	1,5		200	GSG500T-18-nt	18		50
GSG500T-2-nt	2		200	GSG500T-20-nt	20		50
GSG500T-2,5-nt	2,5		200				
GSG500T-3-nt	3		300				
GSG500T-3,5-nt	3,5		300				
GSG500T-4-nt	4		200				
GSG500T-5-nt	5		200				
GSG500T-6-nt	6		100				
GSG500T-7-nt	7		100				
GSG500T-8-nt	8		100				
GSG500T-10-nt	10		50				

Standards and Approvals

RoHS 2002/95/EG, RoHS 2011/65/EU, 2015/863/EU

Please check if this product meets your requirements, and ask for the latest version of this datasheet, before placing any orders. All errors and misprints reserved.